

Ventilated Container

20'

ISO Size Type Code: 22V0



- Especially for cargo which needs ventilation.
- Fork-lift pockets for loaded containers.
- Floor Height 170 mm - 5mm (Ground level to interior floor surface)
- Natural ventilation is provided by openings in top and bottom longitudinal rails.
- The labyrinth construction of these ventilation openings ensures weather-proofness.
- Numerous lashing devices on the top and bottom longitudinal rails and the corner posts. Lashing devices have a permissible load of 1000 kg (2205 lbs) each.

Cigisped: ph: +39 010 815873 fx: +39 010 882393 cigisped@cigisped.it www.cigisped.it

Ventilated Container

Construction	Inside Dimensions			Door Opening		Weights			Capacity m ³ cu.ft
	Length	Width	Height	Width	Height	Max. Gross	Tare	Max. Payload	
	mm ft	mm ft	mm ft	mm ft	mm ft	kg lbs	kg lbs	kg lbs	
8'6" high									
Steel container with corrugated walls and wooden floor	5 888	2 325	2 392	2 334	2 290	30 480	2 400	28 080	33
	19'3 ³ / ₄ "	7'7 ¹ / ₂ "	7'10 ¹ / ₈ "	7'7 ⁷ / ₈ "	7'6 ¹ / ₈ "	67 200	5 290	61 910	1167